

Battery Chargers

Hot Buy!

Charge Pro® Battery Chargers

Guest Charge Pro® battery chargers are built to provide fast, efficient charging in harsh environments. These are proven designs with many years of satisfying owners by charging their batteries quickly and keeping their batteries in excellent shape. Guest chargers are epoxy filled to resist water and dust from damaging the electrical components and extend the charger life in harsh environments.

- Fast charging
- LED's indicates charge status
- Epoxy filled to resist water and dust
- (2) 10 ft cords with ring terminals—(2) 10 ft, 10AWG DC output cables with ring terminals



Part #	Total Amps	Output(s)	Amps/ Output	Battery System	Input Voltage	Dimensions	Wt	Agency Listing	Price
2730-B	30	2	15	12V	100-130V, 60 Hz	6.5"x9.3"x2.5"	8 lbs	UL	\$120.88

Mobility Chargers

Tough, fully automatic chargers meet ANSI-RESNA specifications to provide fast, quiet power for recharging powerchairs and mobility scooters. Portable chargers feature a sleek design and a small footprint for home or institutional use. An inhibit circuit effectively disables the mobility device while charging.

- Resists corrosion and bodily fluids
- Electronics are fully encapsulated in epoxy for protection in hostile environments
- Quiet operation, without the buzz of transformer-based chargers
- Built-in electronic overload and thermal protection
- Short-circuit protected
- Reverse-polarity protected
- Meets FCC Class B requirements for radiated and conducted emissions
- Portable models have standard 3-pin DC XLR connector to fit most mobility devices and IEC connector with power cord
- Use with flooded, AGM and Gel Cell batteries
- 4 ft output cable with XLR connector for DC connection



Part #	Total Amps	Output(s)	Amps/ Output	Battery System	Input Voltage	Dimensions	Wt	Agency Listing	Price
28003	3	1	3	24V	100-130V, 60 Hz	6.6"x7.3"x2.7"	3.3 lbs	UL	\$34.52
28008	8	1	8	24V	100-130V, 60 Hz	7.8"x9.5"x2.9"	6.3 lbs	UL	\$43.16

Battery Chargers Hot Buy!

Charge Pro® Battery Chargers

Guest Charge Pro® battery chargers are built to provide fast, efficient charging in harsh environments. These are proven designs with many years of satisfying owners by charging their batteries quickly and keeping their batteries in excellent shape. Guest chargers are epoxy filled to resist water and dust from damaging the electrical components and extend the charger life in harsh environments.

- Fast charging
- LED indicates charge status
- Epoxy filled to resist water and dust
- 6 ft AC cord with standard plug
- 4 ft DC cable with battery clips



Part #	Total Amps	Output(s)	Amps/ Output	Battery System	Input Voltage	Dimensions	Wt	Agency Listing	Price
2602A-24-B	2	1	2	24V	100-130V, 60 Hz	2.75"x4.50"x1.50"	2 lbs	UL	\$58.96

Charge Pro™ Battery Charger

The GUEST 2903-1-24 is a "3-stage" electronic battery charger. Rainproof, lightweight, silent, and completely automatic, it produces 24 Volts DC at a full 3 Amps, while using much less AC current than older chargers. After it recharges your batteries, it then supplies just enough power to compensate for the charge that batteries can lose during storage. Unlike automotive "trickle" chargers, the 2903-1-24 will not boil off the electrolytes in lead-acid batteries when left unattended. This charger also incorporates an Inhibit signal which can be used to disable external mobility equipment or drive controls when the charger is plugged into the AC wall outlet or AC power is applied to the charger.

- Fast charging
- LED indicates charge status
- Epoxy filled to resist water and dust
- Inhibit output circuitry
- 8 in, 18 AWG, 3 wire input cable terminated with female connector shell
- 6 in, 18 AWG, 3 wire output cable terminated with mate-in-lock connector shell



Part #	Total Amps	Output(s)	Amps/ Output	Battery System	Input Voltage	Dimensions	Wt	Agency Listing	Price
2903-1-24	3	1	3	24V	100-130V, 60 Hz	3.2"x6.2"x2.1"	2.3 lbs	UL	\$34.40

While supplies last.

Standard terms and conditions apply.