

GP 645

6V 4.5Ah

GP 645 is a general purpose battery with 3-5 years in standby service or more than 260 cycles at 100% discharge in cycle service. As with all CSB batteries, all are rechargeable, highly efficient, leak proof and maintenance free.



Specification




Cells Per Unit	3
Voltage Per Unit	6
Capacity	4.5Ah @ 20hr-rate to 1.75V per cell @25 °C (77°F)
Weight	Approx. 0.84kg(1.8 lbs)
Maximum Discharge Current	60A/90A(5sec)
Internal Resistance	Approx. 20mΩ
Operating Temperature Range	Discharge: -20°C~50°C (-4°F~122°F) Charge: 0°C~40°C (32°F~104°F) Storage: -20°C~40°C (-4°F~104°F)
Nominal Operating Temperature Range	25°C±3°C (77°F±5°F)
Float Charging Voltage	6.75 to 6.9 VDC/unit Average at 25°C (77°F)
Recommended Maximum Charging Current Limit	1.35A
Equalization and Cycle Service	7.2 to 7.5 VDC/unit Average at 25°C (77°F)
Self Discharge	CSB Batteries can be stored for more than 6 months at 25°C (77°F). Please charge batteries before using. For higher temperatures the time interval will be shorter.
Terminal	Faston Tab 187/250
Container Material	-ABS (UL94-HB)*Flammability resistance of UL94-V2 can be available upon request.



CSB-manufactured batteries are UL-recognized components under UL924 and UL1989. CSB is also certified by ISO 9001 and ISO 14001.

Dimensions

unit: (MM)



Constant Current Discharge Characteristics Unit:A (25°C, 77°F)


F.V/Time	5MIN	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.60V	18.70	12.30	9.08	5.37	3.11	1.80	1.26	0.99	0.81	0.54	0.44	0.23
1.67V	17.79	11.81	8.91	5.32	3.10	1.79	1.25	0.99	0.81	0.53	0.44	0.23
1.70V	17.40	11.60	8.83	5.30	3.09	1.79	1.25	0.98	0.81	0.53	0.44	0.23
1.75V	16.20	11.15	8.63	5.22	3.06	1.78	1.25	0.98	0.80	0.53	0.43	0.23
1.80V	15.00	10.70	8.42	5.13	3.03	1.76	1.24	0.98	0.80	0.53	0.43	0.23
1.85V	13.80	10.25	8.22	5.05	3.00	1.75	1.24	0.97	0.80	0.53	0.43	0.22

Constant Power Discharge Characteristics Unit:W (25°C, 77°F)


F.V/Time	5MIN	10MIN	15MIN	30MIN	1HR	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.60V	112.00	73.50	54.50	32.20	18.70	10.80	7.55	5.96	4.86	3.21	2.64	1.41
1.67V	107.10	70.70	53.45	31.92	18.63	10.73	7.52	5.94	4.85	3.20	2.63	1.40
1.70V	105.00	69.50	53.00	31.80	18.60	10.70	7.50	5.93	4.84	3.19	2.63	1.40
1.75V	97.50	66.75	51.75	31.30	18.40	10.65	7.48	5.91	4.83	3.18	2.61	1.38
1.80V	90.00	64.00	50.50	30.80	18.20	10.60	7.45	5.89	4.81	3.17	2.59	1.35
1.85V	82.50	61.25	49.25	30.30	18.00	10.55	7.43	5.87	4.80	3.16	2.57	1.33

• All mentioned values are average values.


Trickle (or Float) Service Life




Capacity Retention Characteristic




Battery Voltage and Charge Time for Standby Use




Cycle Service Life



Battery Voltage and Charge Time for Cycle Use



Terminal Voltage (V) and Discharge Time (25°C 77°F)



Charging Procedures

Application	Charge Voltage (V/Cell)			Max. Charge Current
	Temperature	Set Point	Allowable Range	
Cycle Use	25°C (77°F)	2.45	2.40-2.50	0.3C
Standby	25°C (77°F)	2.275	2.25-2.30	

Discharge Current VS. Discharge Voltage

Final Discharge Voltage V/Cell	1.75	1.70	1.55	1.30
Discharge Current (A)	0.2C>(A)	0.2C<(A)<0.5C	0.5C<(A)<1.0C	(A)>1.0C

Sales Office URL: WWW.CSB-BATTERY.COM

CSB BATTERY CO., LTD.
TAIWAN OFFICE
Tel: +886-2-8751-5000
Fax: +886-2-8751-6161
E-mail: service@csb-battery.com.tw

CSB BATTERY OF NETHERLANDS B.V.
NETHERLANDS OFFICE
Tel: +31(0) 180 418 140
Fax: +31(0) 180 418 327
E-mail: eurossales@csb-battery.com

CSB BATTERY (SINGAPORE) PTE., LTD.
SINGAPORE OFFICE
Tel: +65-6742-4944
Fax: +65-6742-4744
E-mail: sales@csb-battery.com.sg

CSB BATTERY TECHNOLOGIES, INC.
USA OFFICE
Tel: +1-817-244-7777/1-8003 CSBUSA(272872)
Fax: +1-817-244-4445
E-mail: csb@csb-battery.com

CSB BATTERY LOGISTICS (SHANGHAI) CO., LTD.
SHANGHAI OFFICE
Tel: +86-21-5046-1622, 5046-0833
Fax: +86-21-5064-3314

CSB BATTERY LOGISTICS (SHANGHAI) CO., LTD.
BEIJING OFFICE
Tel: +86-10-6597-8060, 6597-8070
Fax: +86-10-6597-8050
E-mail: chinasals@csb-battery.com