

• Specifications & Characteristics

Type		UB1229T			
Nominal Voltage		12V			
Rated Capacity		2.9 Ah			
Dimensions	Length	79 ± 1 mm (3.11 ± 0.04 in)			
	Width	59 ± 1 mm (2.32 ± 0.04 in)			
	Container height	99 ± 1 mm (3.90 ± 0.04 in)			
	Height	107 ± 1 mm (4.21 ± 0.04 in)			
Weight		Approx. 1.176 kg (2.59 lbs)			
Capacity 20°C (68°F)	0.05 CA	1.45 A	20 HR	2.9 Ah	
	0.1 CA	0.29 A	10 HR	2.9 Ah	
	0.17 CA	0.493 A	5 HR	2.465 Ah	
	0.2 CA	0.58 A	4 HR	2.32 Ah	
	0.6 CA	1.74 A	1 HR	1.74 Ah	
	1 CA	2.9 A	27 MIN	1.305 Ah	
	3 CA	8.7 A	7 MIN	1.044 Ah	
Internal resistance		Approx. 15 mΩ			
Max. Charging Current		0.87 A			
Charging Voltage 20°C (68°F)	Standby Use	13.5 to 13.8 V (-20mV °C)			
	Cycle Use	14.4 to 15.0 V (-30mV °C)			

